



BOD8903A

2 in 1 oil drainer with tank capacity 90L and inspection chamber



PRODUCT DETAILS

- 2 in 1 oil drainer used for gravity or suction (with vacuum venturi) draining of used oil from engines, gearboxes and differentials of all vehicles
- Includes a 9 litre chamber for immediate visual inspection of the quality of the extracted used oil
- This 9 litre chamber can also be used as a vacuum reservoir
- Includes a wide selection of various probes usable with a wide variety of vehicles, such as a copper probe for high temperature oil
- Flexible nylon: 5 x 700 mm, 6 x 700 mm, 7 x 1000 mm, 8 x 700 mm
- Rigid copper: 5 x 700 mm, 6 x 700 mm
- Adaptors: for BMW, diameter 12.2 mm, and for VAG Group diameter 10 mm
- Suction rate: 1.5 to 2 l/min (oil at 70° and -80°C, with 6 mm probe and 8 bar/115 psi air pressure)
- Suction air pressure: 7-8 bar / 100-115 psi
- Maximum draining pressure: 1 bar / 14.5 psi
- Maximum draining and suction tank capacity: 90 l
- Reinforced connection between tank and oil tube to minimise the risk of leaks
- Swiveling offset funnel design for high flexibility with 18 litre capacity
- Metal reinforced hoses for improved durability
- Foam protected handle for insulation and to avoid scratches on vehicles in case of an accident
- Gauges indicating the level of contained liquid, air tank and suction pressures
- One swivel castor with brake for increased safety
- CE certified

PRODUCT ATTRIBUTES

Product			
BOD8903A	1340-1700 mm	608 mm	36.17 kg

Follow the Fish!

