




8900DM

**3/4" Square Drive Sockets with
Metric Bi-Hex Profile**



PRODUCT DETAILS

- Knurled shank for finger turning of free running fasteners
- Not suitable for machine operation
- Highly polished finish
- High-performance alloy steel
- Standards: ISO 2725/1174 and DIN 3124/3120



Follow the Fish!



PRODUCT ATTRIBUTES

Product		L	D1	D2	T	
8900DM-19	19 mm	52 mm	29.5 mm		12 mm	130 g
8900DM-21	21 mm	52 mm	32 mm	35 mm	13 mm	140 g
8900DM-22	22 mm	47 mm	33 mm	40 mm	14 mm	140 g
8900DM-23	23 mm	50 mm	33.5 mm	40 mm	15 mm	155 g
8900DM-24	24 mm	50 mm	35.5 mm	40 mm	16 mm	175 g
8900DM-25	25 mm	53 mm	36.5 mm	40 mm	16 mm	200 g
8900DM-26	26 mm	53 mm	38.5 mm	40 mm		260 g
8900DM-27	27 mm	53 mm	38.5 mm	40 mm	18 mm	210 g
8900DM-28	28 mm	53 mm	40 mm	40 mm	18 mm	320 g
8900DM-29	29 mm	56 mm	42.5 mm	40 mm	20 mm	270 g
8900DM-30	30 mm	58 mm	42.5 mm	40 mm	20 mm	290 g
8900DM-32	32 mm	58 mm	45 mm	40 mm	22 mm	280 g
8900DM-33	33 mm	60 mm	46.5 mm	40 mm	22 mm	360 g
8900DM-34	34 mm	60 mm	48 mm	40 mm	22 mm	320 g
8900DM-35	35 mm	63 mm	50 mm	40 mm	22 mm	350 g
8900DM-36	36 mm	63 mm	50 mm	40 mm	24 mm	355 g
8900DM-37	37 mm	64 mm	50 mm	40 mm	27 mm	390 g
8900DM-38	38 mm	65 mm	52 mm	44 mm	27 mm	500 g
8900DM-40	40 mm	65 mm	55 mm	40 mm	28 mm	400 g
8900DM-41	41 mm	66 mm	56 mm	40 mm	28 mm	500 g
8900DM-42	42 mm	66 mm	57.5 mm	40 mm	28 mm	465 g
8900DM-46	46 mm	68 mm	62.5 mm	40 mm	31 mm	535 g
8900DM-47	47 mm	68 mm	64.5 mm	40 mm	31 mm	550 g
8900DM-50	50 mm	68 mm	67.5 mm	40 mm	34 mm	580 g
8900DM-52	52 mm	65 mm	70 mm	42 mm	34 mm	590 g
8900DM-54	54 mm	70 mm	74 mm	42 mm	34 mm	740 g
8900DM-55	55 mm	69 mm	74 mm	45 mm	34 mm	830 g
8900DM-56	56 mm	70 mm	75 mm	42 mm	37 mm	900 g
8900DM-60	60 mm	72 mm	80.5 mm	45 mm	37 mm	960 g

Follow the Fish!

